

12 Office & Kitchen>UGR19 Recessed LED Linear Profiles

38145AR/B/W



40W UGR19 Recessed linear with diffuser, ideal for offices. Complete with 1000mA driver , 6pcs fixing clips, 4pcs connectors & 2pcs end cups. .

Complies with standard EN60598-1 and any other specific standards.



<u>55mm</u>

Downloads Dimensions 1210mm 50mm

Gallery



Physical Specification

Item Group 12 Office & Kitchen Family UGR19 Recessed LED Linear Profiles Order Code 38145AR/B/W Colour Black Material Aluminium Diffuser Material PC Shape Rectangular


Length	1210mm
Width	50mm
Height	55mm
Cutout Hole Width	1200mm
Cutout Hole Length	37mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W
Power Factor	0,9
Constant Current	Yes
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	AGT
Illumination Data	
Colour Temperature	3000K
Lumen Output	3800lm

Colour Temperature	3000K
Lumen Output	3800lm
Light Efficiency	95lm/W
CRI	80
Illumination Diagram	
UGR	19

Packing Info	
Pcs/Carton	12
Barcode	5291889067931
HS Code	9405409900

Energy Label



Certification & Warranty	
Warranty	3 Years
Weee Directive	Yes