

38150BR/W/W




Can be connected in line



 IP20 **90** **CRI** DARK LIGHT • UGR17  

Dimensions



Four metal components are shown against a light gray background. At the top are two identical L-shaped brackets, each with a circular hole and a rectangular slot. Below them are two identical rectangular plates, each with three circular holes.

Item Group	12 Office & Kitchen
Family	Recessed LED Linear Profiles
Order Code	38150BR/W/W
Colour	White
Material	Aluminium
Diffuser Material	Plastic
Shape	Rectangular

Length	1300mm
Width	80mm
Height	55mm
Cutout Hole Width	1280mm
Cutout Hole Length	68mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	36V
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 3030
LED Brand	Osram
LED Number	96

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W
Power Factor	0,95
Constant Current	Yes
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Metal
Output Terminal	Connector
Brand	ATG

Illumination Data

Colour Temperature	3000K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	34°
Illumination Diagram	
Dark Light	Yes
UGR	17

Packing Info

Pcs/Carton	12
Barcode	5291889063827
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes