



50116FA/W/C



Complies with standard EN60598-1 and any other specific standards.



Dimensions



super slim!

Physical Specification

06 Downlights Fixed LED

The 8-16W Square Recessed Panels Die cast

Order Code	50116FA/W/C
Colour	White
Material	Die Cast
Diffuser Material	Acrylic
Shape	Rectangular
Length	173mm
Width	173mm
Height	22mm
Cutout Hole Width	155mm
Cutout Hole Length	155mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current

Input Current	350mA
Voltage	42V
Safety Class	
Power(Watts)	14,7W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	84

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9,5-14,7W
Power Factor	0,6
Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	1120lm
Light Efficiency	70lm/W

CRI
Beam Angle
Illumination Diagram


80
120°


Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

23,6cm
18cm
18cm
0,460Kg
30
5291889044291
9405109890

Energy Label



Certification & Warranty

Warranty
Average Lifetime

2 Years
30000 hours

switch to
one light!

one
LIGHT

