

06 Downlights Fixed LED>The SMD Dark Light Range

50122D/W/C



22W Dark Light LED Downlight .

Supplied with 500mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions




Physical Specification

| Item Group | 06 Downlights Fixed LED |
|--------------------|--------------------------|
| Family | The SMD Dark Light Range |
| Order Code | 50122D/W/C |
| Colour | White |
| Material | Die Cast |
| Shape | Rectangular |
| Length | 170mm |
| Width | 170mm |
| Height | 55mm |
| Cutout Hole Width | 160mm |
| Cutout Hole Length | 160mm |
| Recessed Ceiling | Yes |

| Depth Required | 75mm |
|----------------------------|-------------------|
| Indoor | Yes |
| Adjustable | No |
| | |
| Electrical Characteristics | |
| | |
| Gear | External-Included |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 22W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | F |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 500mA |
| Voltage | 40V |
| Safety Class | |
| Power(Watts) | 20W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Sanan |
| | |
| Gear | |
| Gear Type | Led Driver |
| | |

| Input Voltage | 220-240V |
|---|-------------------------------|
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 12,5-20W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 500mA | 25-40V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Ambient Temp | -30? ~ +50? |
| Housing Material | Plastic |
| | Lifud |
| Brand | |
| Ilumination Data | 4000K |
| Ilumination Data Colour Temperature | 4000K 1870lm |
| Ilumination Data Colour Temperature Lumen Output | 1870lm |
| Colour Temperature Lumen Output Light Efficiency | 1870lm 85lm/W |
| Colour Temperature Lumen Output Light Efficiency CRI | 1870lm 85lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle | 1870lm 85lm/W |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram | 1870lm 85lm/W 80 100° |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle | 1870lm 85lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram | 1870lm 85lm/W 80 100° |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light | 1870lm 85lm/W 80 100° |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light | 1870lm 85lm/W 80 100° Yes |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton | 1870lm 85lm/W 80 100° Yes |

Energy Label



Weee Directive

| Certification & Warranty | |
|--------------------------|---------|
| | |
| Warranty | 2 Years |

Yes