

06 Downlights Fixed LED>Square UGR19 Pro Panel

50136P/W/C



UGR
Complete with 900mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Accessories



050108A

Related items



89050L



89050TLD



Physical Specification

Item Group


06 Downlights Fixed LED

Family	Square UGR19 Pro Panel
Order Code	50136P/W/C
Colour	White
Material	Metal
Shape	Rectangular
Length	595mm
Width	595mm
Height	30mm
Recessed T-Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Adjustable	No


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	36W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	900mA
Voltage	35V

Safety Class	
Power(Watts)	31,5W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Samsung

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	22,5-37,8W
Power Factor	0,9
Constant Current	Yes
900mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-30? ~ +50?
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	No-Load, Short Circuit

Illumination Data

Colour Temperature	4000K
Lumen Output	4320lm
Light Efficiency	120lm/W
CRI	80
Beam Angle	120°

Illumination Diagram



UGR

19

Packing Info

Box Weight

2,3Kg

Pcs/Carton

4

Barcode

5291889056751

HS Code

9405409900

Certification & Warranty

Warranty

3 Years

Weee Directive

Yes