


06 Downlights Fixed LED>Rectangular UGR19 Panel

50136RP/W/C



UGR19 LED panel. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with 900mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Accessories



050108B



050150

Related items



89050L



Physical Specification

Item Group


06 Downlights Fixed LED

Family	Rectangular UGR19 Panel
Order Code	50136RP/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	145mm
Height	13mm
Cutout Hole Width	1100mm
Cutout Hole Length	125mm
Recessed Ceiling	Yes
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	36W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting


Input Type	Constant Current
Input Current	900mA
Voltage	35V
Safety Class	
Power(Watts)	31,5W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 4014
LED Brand	Samsung

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	22,5-37,8W
Power Factor	0,9
Constant Current	Yes
900mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-30? ~ +50?
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	No-Load, Short Circuit

Illumination Data


Colour Temperature	4000K
Lumen Output	2900lm

Light Efficiency	80,55lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	
UGR	19

Packing Info

Pcs/Carton	4
Barcode	5291889056775
HS Code	9405109890

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes