

04 Recessed Spots Adjustable LED>The COB Adjustable Spots

51106A/AL/W



COB LED recessed spot. Very elegant design with unique design of the reflector. Ideal for replacing halogen spots.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Adjustable Spots
Order Code	51106A/AL/W
Colour	Aluminium
Material	Aluminium
Shape	Rectangular
Length	92mm
Width	92mm
Height	61mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	80mm

Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	12V
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Brand	Citizen
LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	100-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	6-9W	
Power Factor	0,9	
Constant Current	Yes	
500mA	12-18	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Ambient Temp	-20~50°C	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	HEP	
lumination Data		
lumination Data		
lumination Data Colour Temperature	3000K	
	3000K 475lm	
Colour Temperature		
Colour Temperature Lumen Output	475lm	
Colour Temperature Lumen Output Light Efficiency	475lm 79,16lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	475lm 79,16lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	475lm 79,16lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	475lm 79,16lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	475lm 79,16lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	475lm 79,16lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	475lm 79,16lm/W 80 36° 11,5cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	475lm 79,16lm/W 80 36° 11,5cm 9cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	475lm 79,16lm/W 80 36° 11,5cm 9cm 11,5cm	

Warranty	2 Years
Weee Directive	Yes

Certification & Warranty