

08 Downlights Adjustable LED>The COB Box Type Shop Range

51220/W/C



2x20W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery





Physical Specification


Item Group	08 Downlights Adjustable LED
Family	The COB Box Type Shop Range
Order Code	51220/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	354mm

Width	190mm
Height	100mm
Cutout Hole Width	330mm
Cutout Hole Length	165mm
Recessed Ceiling	Yes
Depth Required	140mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	2x37,3V
Safety Class	<u> </u>
Power(Watts)	2x18,65W
IP Rating	IP20
Light Source	LED built in

LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,5-21W
Power Factor	0,9
Constant Current	Yes
500mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	4000K
	4000K 2x1400lm
Colour Temperature	
Colour Temperature Lumen Output	2x1400lm
Colour Temperature Lumen Output Light Efficiency	2x1400lm 70lm/VV 80 36°
Colour Temperature Lumen Output Light Efficiency CRI	2x1400lm 70lm/VV 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2x1400lm 70lm/VV 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2x1400lm 70lm/VV 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2x1400lm 70lm/W 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	2x1400lm 70lm/W 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	2x1400lm 70lm/W 80 36° 40cm 23cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	2x1400lm 70lm/W 80 36° 40cm 23cm 17cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	2x1400lm 70lm/W 80 36° 40cm 23cm

Pcs/Carton	8
Barcode	5291889041153
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes