

## 15 Plafo>The LED Slim Plafo Range Round

# 62022A/W/W



20W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



### Gallery





#### Physical Specification

Item Group	15 Plafo
Family	The LED Slim Plafo Range Round
Order Code	62022A/W/W
Colour	White
Material	PC
Shape	Circular
Height	55mm


Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	450mA
Voltage	40V
Power(Watts)	18W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	120
F Mark	F

285mm

Diameter

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	11,25-18,9W
Power Factor	0,9
Constant Current	Yes
350mA	25-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Illumination Data	
Colour Temperature	3000K
Colour Temperature  Lumen Output	1600lm
Colour Temperature  Lumen Output  Light Efficiency	1600lm 80lm/VV
Colour Temperature  Lumen Output  Light Efficiency  CRI	1600lm
Colour Temperature  Lumen Output  Light Efficiency	1600lm 80lm/VV
Colour Temperature  Lumen Output  Light Efficiency  CRI	1600lm 80lm/VV
Colour Temperature  Lumen Output  Light Efficiency  CRI	1600lm 80lm/VV
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	1600lm 80lm/VV
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	1600lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	1600lm  80lm/VV  80  29cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	1600lm  80lm/W  80  29cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1600lm 80lm/W 80 29cm 29cm 7,2cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	1600lm  80lm/W  80  29cm  7,2cm  0,8kg

## Energy Label



Certification & Warranty	
Warranty	2 Years

Weee Directive

Yes