

15 Plafo>The LED Decorative Plafo Round

62132N/AN/W



32W LED Decorative Plafo, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	15 Plafo
Family	The LED Decorative Plafo Round
Order Code	62132N/AN/W
Colour	Anthracite
Material	Aluminium
Shape	Circular
Height	132mm
Diameter	455mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	32W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	800mA
Voltage	40V
Power(Watts)	32W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Bridgelux
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	26,4-35,2W

Power Factor	0,9
Constant Current	Yes
800mA	33-44V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	TRIDONIC
When it at the Data	
Illumination Data	
Colour Temperature	3000K
	3000K 2720lm
Colour Temperature	
Colour Temperature Lumen Output	2720lm
Colour Temperature Lumen Output Light Efficiency	2720lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	2720lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	2720lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	2720lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	2720lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	2720lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Pcs/Carton	2720lm 85lm/W 80 1

Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hours
Weee Directive	Yes