

15 Plafo>The LED Decorative Plafo Round

62132N/W/W



32W LED Decorative Plafo, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads






Dimensions




Physical Specification

| | |
|-----------------|--------------------------------|
| Item Group | 15 Plafo |
| Family | The LED Decorative Plafo Round |
| Order Code | 62132N/W/W |
| Colour | White |
| Material | Aluminium |
| Shape | Circular |
| Height | 132mm |
| Diameter | 455mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |


| Gear | External-Included |
|------------------|---|
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 32W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

| Fitting | |
|---------------|---|
| Input Type | Constant Current |
| Input Current | 800mA |
| Voltage | 40V |
| Power(Watts) | 32W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Bridgelux |
| F Mark |  |

| Gear | |
|---------------|------------|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 26,4-35,2W |

| | |
|------------------|---|
| Power Factor | 0,9 |
| Constant Current | Yes |
| 800mA | 33-44V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | TRIDONIC |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 2720lm |
| Light Efficiency | 85lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Pcs/Carton | 1 |
| Barcode | 5291889046790 |
| HS Code | 9405409900 |

Certification & Warranty

Warranty

3 Years

Average Lifetime

30000hours

Weee Directive

Yes
