



15 Plafo>LED Aluminium Panel Range

62140RE/W/C



40W, 120x30cm LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	15 Plafo
Family	LED Aluminium Panel Range
Order Code	62140RE/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	300mm
Height	40mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear		External-Included	
Fitting + Driver			
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	
Safety Class			
Power(Watts)		40W	
IP Rating		IP40	
Light Source		LED built in	
Dimmable		No	
F Mark			
Fitting			
Input Type		Constant Current	
Input Current		1000mA	
Voltage		38V	
Safety Class			
Power(Watts)		38W	
IP Rating		IP40	
Light Source		LED built in	
LED Type		SMD 2835	
LED Brand		Sanan	
F Mark			
Gear			
Gear Type		Led Driver	
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	

Power(Watts)
Power Factor
Constant Current
1000mA
IP Rating
Safety Class
Dimmable
Ambient Temp
Operating Temp
Housing Material
Output Terminal
Fast Connector
Fast Connector Type
Brand

28,5-38W
0,9
Yes
30-40V
IP20

No
40°C
80°C
Plastic
Cable
Yes
Other
AGT

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram

4000K
3600lm
90lm/W
80


Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

133cm
36cm
8,5cm
4Kg
4
5291889052166
9405409900

Warranty	2 Years
Weee Directive	Yes