

## 15 Plafo>The LED Slim Line Plafo

# 62146A/B/W



50W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



### Gallery




#### Physical Specification

Item Group	15 Plafo
Family	The LED Slim Line Plafo
Order Code	62146A/B/W
Colour	Black
Material	Iron
Diffuser Material	Plastic
Shape	Rectangular

Length	500mm
Width	500mm
Height	75mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	100V
Power(Watts)	50W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	55-60W
Power Factor	0,9
Constant Current	Yes
Output	480mA
Voltage Range	100-110V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Illumination Data	
	3000K
Colour Temperature	3000K
Colour Temperature  Lumen Output	4100lm
Colour Temperature  Lumen Output  Light Efficiency	4100lm 82lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	4100lm 82lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	4100lm 82lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	4100lm 82lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4100lm 82lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	4100lm 82lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4100lm 82lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4100lm 82lm/W 80 120°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Pcs/Carton	4100lm 82lm/W 80 120°

# Energy Label



Warranty	3 Years
Weee Directive	Yes