

## 15 Plafo>The LED Slim Line Plafo

# 62146/B/W



55W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads









#### Dimensions



### Gallery




#### Physical Specification

Item Group	15 Plafo
Family	The LED Slim Line Plafo
Order Code	62146/B/W
Colour	Black
Material	Iron
Diffuser Material	Plastic
Shape	Circular

Height	75mm
Diameter	550mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	55W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	90V
Power(Watts)	54W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	F

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	54-60W
Power Factor	0,9
Constant Current	Yes
600mA	90-100V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Ilumination Data	
Colour Temperature	3000K
Colour Temperature  Lumen Output	3000K 4100lm
Lumen Output	4100lm
Lumen Output Light Efficiency	4100lm 74,57lm/W
Lumen Output Light Efficiency CRI	4100lm
Lumen Output  Light Efficiency  CRI  Beam Angle	4100lm 74,57lm/W 80
Lumen Output Light Efficiency CRI	4100lm 74,57lm/W 80
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4100lm 74,57lm/W 80
Lumen Output  Light Efficiency  CRI  Beam Angle	4100lm 74,57lm/W 80
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4100lm 74,57lm/W 80
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4100lm 74,57lm/W 80 120°

# Energy Label



Certification & Warranty		

Warranty	3 Years
Weee Directive	Yes