

New 2021 Edition 2>Plafo

62146/W/W



55W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery




Physical Specification

Item Group	New 2021 Edition 2
Family	Plafo
Order Code	62146/W/W
Colour	White
Material	Iron
Diffuser Material	Plastic
Shape	Circular

Height	75mm
Diameter	550mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
ectrical Characteristics	
Gear	Built In
End and Different Control	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	55W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	90V
Power(Watts)	54W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	F

Gear		
Gear Type	Led Driver	
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	54-60W	
Power Factor	0,9	
Constant Current	Yes	
600mA	90-100V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Ilumination Data		
Colour Temperature	3000K	
Colour Temperature Lumen Output	3000K 4100lm	
Lumen Output	4100lm	
Lumen Output Light Efficiency	4100lm 74,57lm/W	
Lumen Output Light Efficiency CRI	4100lm	
Lumen Output Light Efficiency CRI Beam Angle	4100lm 74,57lm/W 80	
Lumen Output Light Efficiency CRI	4100lm 74,57lm/W 80	
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4100lm 74,57lm/W 80	
Lumen Output Light Efficiency CRI Beam Angle	4100lm 74,57lm/W 80	
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4100lm 74,57lm/W 80	
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4100lm 74,57lm/W 80 120°	

Energy Label



Certification & Warranty		

Warranty	3 Years
Weee Directive	Yes