

15 Plafo>The Super Slim LED Plafo

62152A/B/W



40W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|-----------------|--------------------------|
| Item Group | 15 Plafo |
| Family | The Super Slim LED Plafo |
| Order Code | 62152A/B/W |
| Colour | Black |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 620mm |
| Width | 620mm |
| Height | 33mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

40W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

900mA

Voltage

43V

Power(Watts)

38,7W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz


Yes

60 Hz


Yes

Power(Watts)

27-40,5W

| | |
|------------------|---|
| Power Factor | 0,9 |
| Constant Current | Yes |
| 900mA | 30-45V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | 3AAA |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 2800lm |
| Light Efficiency | 70lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Pcs/Carton | 5 |
| Barcode | 5291889063421 |
| HS Code | 9405409900 |

Energy Label



Warranty

3 Years

Weee Directive

Yes
