

15 Plafo>The Super Slim LED Plafo

62152A/W/C



40W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	15 Plafo
Family	The Super Slim LED Plafo
Order Code	62152A/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	620mm
Width	620mm
Height	33mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	900mA
Input Current Voltage	900mA 43V
Voltage	43V
Voltage Power(Watts)	43V 38,7W
Voltage Power(Watts) IP Rating	43V 38,7W IP20
Voltage Power(Watts) IP Rating Light Source	43V 38,7W IP20 LED built in
Voltage Power(Watts) IP Rating Light Source LED Type	43V 38,7W IP20 LED built in SMD 2835
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand	38,7W IP20 LED built in SMD 2835 Sanan
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand	38,7W IP20 LED built in SMD 2835 Sanan
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand F Mark	38,7W IP20 LED built in SMD 2835 Sanan
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand F Mark Gear	38,7W IP20 LED built in SMD 2835 Sanan F
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand F Mark Gear Gear Type	43V 38,7W IP20 LED built in SMD 2835 Sanan F Led Driver
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand F Mark Gear Gear Type Input Voltage	43V 38,7W IP20 LED built in SMD 2835 Sanan F Led Driver 220-240V
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand F Mark Gear Gear Gear Type Input Voltage 50 Hz	43V 38,7W IP20 LED built in SMD 2835 Sanan F Led Driver 220-240V Yes


Power Factor	0,9
Constant Current	Yes
900mA	30-45V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	3AAA

Illumination Data

Colour Temperature	4000K
Lumen Output	2800lm
Light Efficiency	70lm/W
CRI	80
Illumination Diagram	

Packing Info Pcs/Carton 5 Barcode 5291889063476 HS Code 9405409900

Energy Label



Warranty	3 Years
Weee Directive	Yes

Certification & Warranty