

10 Track Spots>Adjustable LED Linear Track Light

65024T/W/W



10X5W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.





Downloads









Dimensions



Related items







40003A/W

Physical Specification

Item Group	10 Track Spots
Family	Adjustable LED Linear Track Light
Order Code	65024T/W/W
Colour	White
Material	Aluminium + Plastic
Shape	Rectangular
Length	580mm

Width	60mm
Height	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10x5W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1200mA
Voltage	38V
Power(Watts)	45,6W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	10

Gear

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	39,6-50,4W
Power Factor	0,9
Constant Current	Yes
1200mA	33-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	LIFUD
Protection	Short Circuit Protection
Ilumination Data	
	000014
Colour Temperature	3000K
Colour Temperature Lumen Output	10x580lm
Colour Temperature Lumen Output Light Efficiency	10x580lm 116lm/W
Colour Temperature Lumen Output Light Efficiency CRI	10x580lm 116lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	10x580lm 116lm/W
Colour Temperature Lumen Output Light Efficiency CRI	10x580lm 116lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	10x580lm 116lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	10x580lm 116lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	10x580lm 116lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	10x580lm 116lm/VV 80 30°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	10x580lm 116lm/W 80 30° 51,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	10x580lm 116lm/W 80 30° 51,5cm 9cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	10x580lm 116lm/W 80 30° 51,5cm 9cm 13cm

Led Driver

Gear Type

Energy Label



Energy Class	D
Energy Consumption	50KWh/1000h

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes