

10 Track Spots>The Track Floodlight Range

65042T/W/W



42W LED floodlight range track light, high lumen output ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Related items





40003A/W

Physical Specification

Item Group

10 Track Spots

Family

The Track Floodlight Range


| Order Code | 65042T/W/W |
|--|---|
| Colour | White |
| Material | Die Cast |
| Shape | Rectangular |
| Length | 184mm |
| Width | 107mm |
| Height | 255mm |
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |
| lectrical Characteristics Gear | Built In |
| | Built In |
| | Built In |
| Gear | Built In 220-240V |
| Gear Fitting + Driver | |
| Gear Fitting + Driver Input Voltage | 220-240V |
| Gear Fitting + Driver Input Voltage 50 Hz | 220-240V Yes |
| Gear Fitting + Driver Input Voltage 50 Hz 60 Hz | 220-240V Yes |
| Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class | 220-240V Yes Yes |
| Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) | 220-240V Yes Yes 42W |
| Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating | 220-240V Yes Yes 42W IP20 |
| Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source | 220-240V Yes Yes 42W IP20 LED built in |
| Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source | 220-240V Yes Yes 42W IP20 LED built in |

| Dimmable | No | |
|---------------|------------------|--|
| | | |
| Fitting | | |
| Input Type | Constant Current | |
| Input Current | 1200mA | |
| Voltage | 33V | |
| Power(Watts) | 39,6W | |
| IP Rating | IP20 | |
| Light Source | LED built in | |
| | | |

| LED Type | SMD 2835 |
|----------------------|--------------------------|
| LED Brand | Sanan |
| | |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 32,4-50,4W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 1200mA | 27-42V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | Lifud |
| Protection | Short Circuit Protection |
| | |
| Illumination Data | |
| Colour Temperature | 3000K |
| Lumen Output | 3150lm |
| Light Efficiency | 75lm/W |
| CRI | 80 |
| Beam Angle | 80° |
| Illumination Diagram | |
| | |
| Packing Info | |
| | |
| Box Length | 30cm |

| Box Width | 23cm |
|------------|---------------|
| Box Height | 10,5cm |
| Box Weight | 1,9Kg |
| Pcs/Carton | 4 |
| Barcode | 5291889043805 |
| HS Code | 9405409900 |

Energy Label



Certification & Warranty

| Warranty | 2 Years |
|----------------|---------|
| Weee Directive | Yes |
| | |