

10 Track Spots>Cylindrical Track Spot

65608T/G/W



3x1W LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.




Downloads






Dimensions



Related items



40003A/G


Physical Specification

Product Type	Gear
Item Group	10 Track Spots
Family	Cylindrical Track Spot
Order Code	65608T/G/W
Colour	Grey
Material	Die Cast
Shape	Circular

Height	170mm
Diameter	55mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	3W
Power Factor	0,5
Constant Current	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Manufacturer	Eaglerise
Protection	Short Circuit Protection
lumination Data	
lumination Data	
lumination Data Colour Temperature	3000K
	3000K 205lm
Colour Temperature	
Colour Temperature Lumen Output	205lm
Colour Temperature Lumen Output Light Efficiency	205lm 68,33lm/W
Colour Temperature Lumen Output Light Efficiency Beam Angle	205lm 68,33lm/W 60°
Colour Temperature Lumen Output Light Efficiency Beam Angle	205lm 68,33lm/W 60°
Colour Temperature Lumen Output Light Efficiency Beam Angle	205lm 68,33lm/W 60°
Colour Temperature Lumen Output Light Efficiency Beam Angle Illumination Diagram	205lm 68,33lm/W 60°
Colour Temperature Lumen Output Light Efficiency Beam Angle Illumination Diagram acking Info	205lm 68,33lm/W 60°

Energy Label



Warranty	2 Years
Wee Directive	Yes

Certification & Warranty