

10 Track Spots>The Black Heatsink Range

65620T/W/W



20W COB LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



Related items







40003A/W


Physical Specification

Item Group	10 Track Spots
Family	The Black Heatsink Range
Order Code	65620T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	210mm

Diameter	102mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Coor	Duille lo
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	28V
Power(Watts)	19W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

Power (Watts)	50 Hz	Yes
Power Factor	60 Hz	Yes
Soloma	Power(Watts)	13,5-21W
Paking IP20 IP20 Safety Class □	Power Factor	0,9
IP Rating	Constant Current	Yes
Safety Class □ Dimmable No Housing Material Plastic Output Terminal Connector Brand Lifud Protection Short Circuit Protection Illumination Data 3000K Lumen Output 1460lm Light Efficiency 73lmW CRI 80 Boam Angle 45° Illumination Diagram No Packing Info 27cm Box Weight 18cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	500mA	27-42V
Dimmable	IP Rating	IP20
Housing Material	Safety Class	
Output Terminal Connector Brand Lifud Protection Short Circuit Protection Illumination Data Colour Temperature 30000K Lumen Output 1460lm Light Efficiency 73lm/W CRI 80 Beam Angle 45° Illumination Diagram Term Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	Dimmable	No
Brand Lifud Protection Short Circuit Protection Illumination Data Colour Temperature 3000K Lumen Output 1460lm Light Efficiency 73lm/W CRI 80 Beam Angle 45° Illumination Diagram N Packing Info 27cm Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	Housing Material	Plastic
Protection Short Circuit Protection	Output Terminal	Connector
Colour Temperature	Brand	Lifud
Colour Temperature 3000K Lumen Output 1460lm Light Efficiency 73lm/W CRI 80 Beam Angle 45° Illumination Diagram	Protection	Short Circuit Protection
Colour Temperature 3000K Lumen Output 1460lm Light Efficiency 73lm/W CRI 80 Beam Angle 45° Illumination Diagram		
Lumen Output 1460Im Light Efficiency 73Im/W CRI 80 Beam Angle 45° Illumination Diagram Illumination Diagram Packing Info 27cm Box Length 18cm Box Width 18cm Box Height 12cm Pcs/Carton 12 Barcode 5291889043843	Illumination Data	
Lumen Output 1460Im Light Efficiency 73Im/W CRI 80 Beam Angle 45° Illumination Diagram Illumination Diagram Packing Info 27cm Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843		
Light Efficiency 73lm/W CRI 80 Beam Angle 45° Illumination Diagram		
CRI 80 Beam Angle 45° Illumination Diagram Illumination Diagram Packing Info 27cm Box Length Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843		
Beam Angle 45° Illumination Diagram Illumination Diagram Packing Info Box Length Box Length Box Width 18cm Box Height 12cm Box Weight Pcs/Carton 12 Barcode 5291889043843		73lm/W
Packing Info Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	CRI	80
Packing Info 27cm Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	Beam Angle	45°
Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	Illumination Diagram	
Box Length 27cm Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843		
Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	Packing Info	
Box Width 18cm Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843	Box Length	27cm
Box Height 12cm Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843		
Box Weight 0,93Kg Pcs/Carton 12 Barcode 5291889043843		
Pcs/Carton 12 Barcode 5291889043843		
Barcode 5291889043843		
74U04U33UU		
	110 Code	

Energy Label



Certification	& W	/arrantv
Columbation	\sim $^{\prime}$	arrarrey

Warranty	2 Years
Weee Directive	Yes