

# 10 Track Spots>The COB Side Box Range

# 65626T/W/W



25W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



### Downloads









### Dimensions



### Gallery



### Related items







40003A/W

### **Physical Specification**

Item Group

10 Track Spots

Family

The COB Side Box Range

Order Code	65626T/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	90mm
Width	90mm
Height	232mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
0.5.5.5	Desité les
Gear	Built In
Gear Fitting + Driver	Built In
	Built In  100-240V
Fitting + Driver	
Fitting + Driver Input Voltage	100-240V
Fitting + Driver  Input Voltage  50 Hz	100-240V Yes
Fitting + Driver  Input Voltage  50 Hz  60 Hz	100-240V Yes
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class	100-240V Yes Yes
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)	100-240V Yes Yes  25W
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating	100-240V Yes Yes 25W IP20
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source	100-240V  Yes  Yes  25W  IP20  LED built in
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source	100-240V  Yes  Yes  25W  IP20  LED built in
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable	100-240V  Yes  Yes  25W  IP20  LED built in


Fitting	
Input Type	Constant Current
Input Current	580mA
Voltage	38V
Power(Watts)	22W
IP Rating	IP20
Light Source	LED built in

LED Type	COB
LED Brand	Sharp
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	20-22W
Power Factor	0,9
Constant Current	Yes
Output	580mA
Voltage Range	35-38V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
Protection	Short Circuit Protection
Illumination Data	
Colour Temperature	3000K
Lumen Output	1900lm
Light Efficiency	76lm/W
CRI	450
Beam Angle	45°
Illumination Diagram	

# Box Length 28cm Box Width 12cm Box Height 18,5cm Box Weight 1,1kg Pcs/Carton 12 Barcode 5291889043249 HS Code 9405409900

# Energy Label

Packing Info



## Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hours
Weee Directive	Yes