

### 10 Track Spots>The Black Heatsink Range

# 65628T/B/W



15W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads









#### Dimensions



#### Related items







40003A/B

### Physical Specification


Item Group	10 Track Spots
Family	The Black Heatsink Range
Order Code	65628T/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	132mm

Diameter	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	Built In
Eitting I Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	400mA
Voltage	35V
Power(Watts)	14W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	12-18W
Power Factor	0,9
Constant Current	Yes
400mA	30-45V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
Protection	Short Circuit Protection
Illumination Data	200014
Colour Temperature	3000K
Colour Temperature  Lumen Output	1095lm
Colour Temperature  Lumen Output  Light Efficiency	1095lm 73lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	1095lm 73lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1095lm 73lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	1095lm 73lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1095lm 73lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1095lm 73lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1095lm 73lm/VV 80 45°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1095lm 73lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	1095lm 73lm/W 80 45°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	1095lm 73lm/W 80 45° 20cm 11,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1095lm 73lm/W 80 45°  20cm 11,5cm 10cm

Barcode	5291889043928
HS Code	9405409900

### Energy Label



## Certification & Warranty

Warranty	2 Years
Average Lifetime	30000hours
Weee Directive	Yes