

10 Track Spots>The COB Cylinder Range

65632CT/B/W



50W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/B

Physical Specification


Item Group	10 Track Spots
Family	The COB Cylinder Range
Order Code	65632CT/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	160mm

Diameter	130mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1250mA
Voltage	37V
Safety Class	(III)
Power(Watts)	46,25W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Cree
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24-52,5W
Power Factor	0,9
Constant Current	Yes
1250mA	37-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~50°C
Operating Temp	90°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Tridonic
Protection	Short Circuit Protection
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	3000K
	3000K 3750lm
Colour Temperature	
Colour Temperature Lumen Output	3750lm
Colour Temperature Lumen Output Light Efficiency	3750lm 75lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3750lm 75lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3750lm 75lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3750lm 75lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3750lm 75lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3750lm 75lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3750lm 75lm/W 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3750lm 75lm/W 80 36° 32,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3750lm 75lm/W 80 36° 32,5cm

Pcs/Carton	6
Barcode	5291889047773
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Average Lifetime	30000hours
Weee Directive	Yes