

### 14 Wall & Ceiling LED>Reading Spots Aluminium

# 65746B/W/W



3W COB LED bedside adjustable fitting with 5W backlight and switch, ideal for room hotel installation, IP20.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



#### Gallery



#### **Physical Specification**


14 Wall & Ceiling LED
Reading Spots Aluminium
65746B/W/W
White
Aluminium
Circular
32mm

Diameter	148mm
Surface Wall	Yes
Indoor	Yes
Adjustable	2 Directions
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W + 5W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA+350mA
Voltage	4V/14V
Safety Class	
Power(Watts)	2,8W/4,9W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Samsung

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1,75-2,8W/4,2-6,3W
Power Factor	0,5
Constant Current	Yes
350mA	12-18V
700mA	2,5-4V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	Eaglerise
llumination Data	
llumination Data	
llumination Data  Colour Temperature	3000K
	3000K 150lm
Colour Temperature	
Colour Temperature  Lumen Output	150lm
Colour Temperature  Lumen Output  Light Efficiency	150lm 50lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	150lm 50lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	150lm 50lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	150lm 50lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	150lm 50lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	150lm 50lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	150lm/VV 80 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Pcs/Carton	150lm 50lm/W 80 36°

## Energy Label



Weee Directive

Certification & Warranty	
Warranty	2 Years

Yes