

20 Garden & Underwater>The LED Bollards

67250/G/D



2x3W LED Bollard, IP54 for Garden illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification


Item Group	20 Garden & Underwater
Family	The LED Bollards
Order Code	67250/G/D
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Rectangular
Length	80mm
Width	45mm
Height	650mm
Surface Floor/Ground	Yes
Outdoor	Yes

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x3W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
IP Rating	IP65
IP Rating	IP65
IP Rating	IP65
IP Rating Light Source	IP65
IP Rating Light Source Gear	IP65 LED built in
IP Rating Light Source Gear Gear Type	LED built in Led Driver
IP Rating Light Source Gear Gear Type Input Voltage	LED built in Led Driver 220-240V
IP Rating Light Source Gear Gear Type Input Voltage 50 Hz	LED built in Led Driver 220-240V Yes
IP Rating Light Source Gear Gear Type Input Voltage 50 Hz 60 Hz	LED built in Led Driver 220-240V Yes Yes
IP Rating Light Source Gear Gear Type Input Voltage 50 Hz 60 Hz Power(Watts)	LED built in Led Driver 220-240V Yes Yes 6W
IP Rating Light Source Gear Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor	LED built in Led Driver 220-240V Yes Yes 6W 0,9
IP Rating Light Source Gear Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor Constant Current	LED built in Led Driver 220-240V Yes Yes 6W 0,9 Yes

Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Protection	Short Circuit	
Illumination Data		
Colour Temperature	6000K	
Illumination Diagram		
Dark Light	Yes	
Packing Info		
Pcs/Carton	8	
Barcode	5291889018896	
HS Code	9405409900	

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes