

# 22 Emergency Lights>Emergency LED Plafo

# 67280ANE/G/W



15W Emergency LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads









## Dimensions




### **Physical Specification**

Item Group	22 Emergency Lights
Family	Emergency LED Plafo
Order Code	67280ANE/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	75mm
Diameter	300mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

Power(Watts)	10-16W
Power Factor	0,9
Constant Current	Yes
300mA	35-50V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Ilumination Data	
Colour Temperature	3000K
Lumen Output	1000lm
Light Efficiency	66,67lm/W
CRI	80
CRI Illumination Diagram	80
	80
Illumination Diagram	80
	80
Illumination Diagram	80 
Illumination Diagram Packing Info	
Illumination Diagram  Packing Info  Box Length	31cm
Illumination Diagram  Packing Info  Box Length  Box Width	31cm 31cm
Packing Info  Box Length  Box Width  Box Height	31cm 31cm 8,5cm
Packing Info  Box Length  Box Width  Box Height  Box Weight	31cm 31cm 8,5cm 1,4Kg
Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton	31cm 31cm 8,5cm 1,4Kg

# Energy Label



Weee Directive

Certification & Warranty	
Warranty	2 Years

Yes