

15 Plafo>The LED Plafo Outdoor Round

67280AN/W/C



24W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

|                   |                             |
|-------------------|-----------------------------|
| Item Group        | 15 Plafo                    |
| Family            | The LED Plafo Outdoor Round |
| Order Code        | 67280AN/W/C                 |
| Colour            | White                       |
| Material          | Plastic                     |
| Diffuser Material | PC                          |
| Shape             | Circular                    |
| Height            | 83mm                        |
| Diameter          | 300mm                       |
| Surface Ceiling   | Yes                         |
| Indoor            | Yes                         |
| Outdoor           | Yes                         |

Adjustable

No

IK Rating

8

## Electrical Characteristics

Gear

Built In

### Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

24W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



### Fitting

Input Type

Constant Current

Input Current

600mA

Voltage

38V

Power(Watts)

22,8W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

LED Number

121


F Mark




Gear

Gear Type

Led Driver

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| Input Voltage    | 220-240V                                                                            |
| 50 Hz            | Yes                                                                                 |
| 60 Hz            | Yes                                                                                 |
| Power(Watts)     | 15,6-26W                                                                            |
| Power Factor     | 0,9                                                                                 |
| Constant Current | Yes                                                                                 |
| 600mA            | 26-43,5V                                                                            |
| IP Rating        | IP20                                                                                |
| Safety Class     |  |
| Dimmable         | No                                                                                  |
| Housing Material | Plastic                                                                             |
| Output Terminal  | Connector                                                                           |
| Brand            | Eaglerise                                                                           |

#### Illumination Data

|                      |                                                                                       |
|----------------------|---------------------------------------------------------------------------------------|
| Colour Temperature   | 4000K                                                                                 |
| Lumen Output         | 1440lm                                                                                |
| Light Efficiency     | 60lm/W                                                                                |
| CRI                  | 80                                                                                    |
| Illumination Diagram |  |

#### Packing Info

|            |               |
|------------|---------------|
| Box Length | 30,5cm        |
| Box Width  | 30,5cm        |
| Box Height | 8,5cm         |
| Box Weight | 1,2Kg         |
| Pcs/Carton | 10            |
| Barcode    | 5291889043317 |
| HS Code    | 9405104090    |



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes