

15 Plafo>The LED Plafo Outdoor Square Plastic

67282AN/G/W



24W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Square Plastic
Order Code	67282AN/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	295mm
Width	295mm
Height	80mm
Surface Ceiling	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	No
IK Rating	8
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	38V
Power(Watts)	22,8W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver

50 Hz	Yes
60 Hz	Yes
Power(Watts)	15,6-26W
Power Factor	0,9
Constant Current	Yes
600mA	26-43,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Illumination Data	
	20001
Colour Temperature	3000K 1440lm
Colour Temperature Lumen Output	1440lm
Colour Temperature Lumen Output Light Efficiency	1440lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1440lm
Colour Temperature Lumen Output Light Efficiency	1440lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1440lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	1440lm 60lm/W 80 30,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	1440lm 60lm/W 80 30,5cm 30,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	30,5cm 30,5cm 8,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	30,5cm 30,5cm 8,5cm 1,4Kg

Energy Label



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes