

15 Plafo>The LED Plafo Outdoor Square Plastic

67282N/G/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Square Plastic
Order Code	67282N/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	221mm
Width	221mm
Height	57mm
Surface Ceiling	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	81
F Mark	F
Gear	

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-16W
Power Factor	0,9
Constant Current	Yes
500mA	19-32V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Illumination Data	
marini dueri Bala	
	20001/
Colour Temperature	3000K
Colour Temperature Lumen Output	960lm
Colour Temperature Lumen Output Light Efficiency	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	960lm
Colour Temperature Lumen Output Light Efficiency	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	960lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	960lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	960lm 60lm/W 80 23cm 23cm 6,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	960lm 60lm/W 80 23cm 23cm 6,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	960lm 60lm/W 80 23cm 23cm 6,5cm 0,8Kg

Energy Label



Certification	& W	/arrantv
Columbation	\sim $^{\prime}$	arrarrey

Warranty	2 Years
Weee Directive	Yes