

15 Plafo>The LED Slim Plafo Range PC

67370/W/W



25W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	15 Plafo
Family	The LED Slim Plafo Range PC
Order Code	67370/W/W
Colour	White
Material	PC
Shape	Circular
Height	40mm
Diameter	350mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

## Electrical Characteristics

## Gear

## Built In

## Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

25W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



## Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

80V

Power(Watts)

24W

IP Rating

IP54

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

LED Number

335

F Mark



## Gear

Gear Type


Led Driver

Input Voltage

100-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	18,6-24,8W
Power Factor	0,9
Constant Current	Yes
Output	310mA
Voltage Range	60-80V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable


#### Illumination Data

Colour Temperature	3000K
Lumen Output	1875lm
Light Efficiency	85lm/W
CRI	80
Illumination Diagram	

#### Packing Info

Box Length	36cm
Box Width	36cm
Box Height	5cm
Box Weight	1,4kg
Pcs/Carton	10
Barcode	5291889043096
HS Code	9405104090

#### Energy Label



## Certification & Warranty

Warranty

2 Years

Weee Directive

Yes