

15 Plafo>The LED Slim Plafo Range PC

67372/W/W



25W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	15 Plafo
Family	The LED Slim Plafo Range PC
Order Code	67372/W/W
Colour	White
Material	PC
Shape	Rectangular
Length	300mm
Width	300mm
Height	40mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable

No

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

25W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

80V

Power(Watts)

24W

IP Rating

IP54

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

LED Number

335

F Mark



Gear

Gear Type


Led Driver

Input Voltage

100-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	18,6-24,8W
Power Factor	0,9
Constant Current	Yes
Output	310mA
Voltage Range	60-80V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable

Illumination Data

Colour Temperature	3000K
Lumen Output	1875lm
Light Efficiency	75lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	31cm
Box Width	31cm
Box Height	5cm
Box Weight	1,2kg
Pcs/Carton	10
Barcode	5291889043157
HS Code	9405104090

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes