

14 Wall & Ceiling LED>Outdoor Slim Oval Range Up & down beam

67378A/W/W



2x6W LED wall light, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	Outdoor Slim Oval Range Up & down beam
Order Code	67378A/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	200mm
Width	110mm
Height	52mm
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

2x6W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

38V

Power(Watts)

11,4W

IP Rating

IP54

Light Source

LED built in

LED Type

SMD 5630

LED Brand

Edison

LED Number

24

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz


Yes

60 Hz


Yes

Power(Watts)

7,8-12W

Power Factor	0,5
Constant Current	Yes
300mA	26-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Housing Material	Plastic
Output Terminal	Cable
Manufacturer	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	2x420lm
Light Efficiency	70lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	12cm
Box Width	6cm
Box Height	21cm
Box Weight	0,7Kg
Pcs/Carton	12
Barcode	5291889043683
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes