

14 Wall & Ceiling LED>COB Outdoor Ceiling Cylinders

67380A/W/W



25W COB LED cylinder, IP54, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	COB Outdoor Ceiling Cylinders
Order Code	67380A/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	160mm

Diameter	120mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

## Electrical Characteristics


Gear	Built In
------	----------

### Fitting + Driver

Input Voltage	100-240V
---------------	----------

50 Hz	Yes
-------	-----

60 Hz	Yes
-------	-----

Safety Class	
--------------	---

Power(Watts)	25W
--------------	-----

IP Rating	IP54
-----------	------

Light Source	LED built in
--------------	--------------

Dimmable	No
----------	----

F Mark	
--------	---

### Fitting

Input Type	Constant Current
------------	------------------

Input Current	600mA
---------------	-------

Voltage	38V
---------	-----

Power(Watts)	22,8W
--------------	-------

IP Rating	IP54
-----------	------


Light Source	LED built in
--------------	--------------

LED Type	COB
----------	-----


LED Brand	Osram
-----------	-------

### Gear

Gear Type	Led Driver
-----------	------------

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-24W
Power Factor	0,9
Constant Current	Yes
600mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

### Illumination Data

Colour Temperature	3000K
Lumen Output	1800lm
Light Efficiency	72lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	

### Packing Info

Pcs/Carton	12
Barcode	5291889044987
HS Code	9405409900

### Energy Label



## Certification & Warranty

Warranty

2 Years

Weee Directive

Yes