

14 Wall & Ceiling LED>The Roof tile Range Die cast

67422A/AN/W



2x6W COB LED Outdoor Slim Range Up & down beam.

Complete with driver


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|--------------|------------------------------|
| Item Group | 14 Wall & Ceiling LED |
| Family | The Roof tile Range Die cast |
| Order Code | 67422A/AN/W |
| Colour | Anthracite |
| Material | Die Cast |
| Shape | Rectangular |
| Length | 190mm |
| Width | 120mm |
| Height | 50mm |
| Surface Wall | Yes |
| Indoor | Yes |
| Outdoor | Yes |

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

2x6W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

20V

Power(Watts)

10W

IP Rating

IP54

Light Source

LED built in

LED Type

COB

LED Brand

Edison

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)


6-12W

Power Factor

0,5

| | |
|------------------|---|
| Constant Current | Yes |
| 500mA | 12-24V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Ambient Temp | 50°C |
| Operating Temp | 75°C |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Manufacturer | Eaglerise |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 2x400lm |
| Light Efficiency | 66,67lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Length | 13cm |
| Box Width | 5,5cm |
| Box Height | 21cm |
| Box Weight | 0,71Kg |
| Pcs/Carton | 12 |
| Barcode | 5291889053026 |
| HS Code | 9405409900 |

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes