

14 Wall & Ceiling LED>Window Frame Illumination

67454/AN/W



6W LED for window frame illumination, IP65.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	Window Frame Illumination
Order Code	67454/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	140mm


Width	95mm
Height	62mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
IK Rating	8
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	11V

Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	11V
Power(Watts)	5,5W
IP Rating	IP65
Light Source	LED built in
LED Type	СОВ

LED Brand	Cree
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3-6W
Power Factor	0,5
Constant Current	Yes
500mA	6-12V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Manufacturer	Eaglerise
Illumination Data	
	20001/
Colour Temperature	3000K
Colour Temperature Lumen Output	330lm
Colour Temperature Lumen Output Light Efficiency	330lm 55lm/W
Colour Temperature Lumen Output Light Efficiency CRI	330lm 55lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	330lm 55lm/W
Colour Temperature Lumen Output Light Efficiency CRI	330lm 55lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	330lm 55lm/W 80 270°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	330lm 55lm/W 80 270°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	330lm 55lm/W 80 270°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	330lm 55lm/VV 80 270°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	330lm 55lm/W 80 270° 270°

Pcs/Carton	18
Barcode	5291889058199
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes