

14 Wall & Ceiling LED>The Backlight Wall Range Aluminium

67466C/B/W



12W LED wall surface light IP20.

Complete 300mA driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	The Backlight Wall Range Aluminium
Order Code	67466C/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	370mm
Width	100mm
Height	80mm
Surface Wall	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	38V
Safety Class	
Power(Watts)	11,4W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Edison
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	7,5-12,6W
Power Factor	0,5
Constant Current	Yes
300mA	25-42V
IP Rating	IP20
Safety Class	
Housing Material	Plastic
Brand	Eaglerise
Protection	0
Illumination Data	
Colour Temperature	3000K
Colour Temperature Lumen Output	3000K 800lm
Lumen Output	800lm
Lumen Output Light Efficiency	800lm 66,67lm/W
Lumen Output Light Efficiency CRI	800lm 66,67lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	800lm 66,67lm/W
Lumen Output Light Efficiency CRI	800lm 66,67lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	800lm 66,67lm/W
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info	800lm 66,67lm/VV 80
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Pcs/Carton	800lm 66,67lm/W 80

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes