

New 2021 Edition 2>Wall & Ceiling LED

67516A/W/W



15W COB LED cylinder, IP65, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	New 2021 Edition 2
Family	Wall & Ceiling LED
Order Code	67516A/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	127mm
Diameter	83mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

15W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

350mA

Voltage

36V

Power(Watts)

12,6W

IP Rating

IP65

Light Source

LED built in

LED Type

COB

LED Brand

Bridgelux

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

10,8-16W

Power Factor

0,9

Constant Current
400mA
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes
27-40V
IP20

No
Plastic
KEGU

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram
Dark Light

3000K
1200lm
80lm/W
90
40°

Yes

Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

9cm
9cm
16cm
24
5291889070108
9405409900

Warranty

2 Years

Weee Directive

Yes
