

19 Wall Recessed & Inground>Dark Light Wall Recessed

68006N/W



1W, Indoor and outdoor wall recessed LED light, ideal for step and corridor illumination.

Supplied complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads











Dimensions




Gallery




Must be ordered separately




050176/B



050176/BBS



050176/G



050176/W

Physical Specification	
Item Group	19 Wall Recessed & Inground
Family	Dark Light Wall Recessed
Order Code	68006N/W
Material	Die Cast
Shape	Rectangular
Length	85mm
Width	85mm
Height	32mm
Cutout Hole Width	70mm
Cutout Hole Length	70mm
Recessed wall	Yes
Depth Required	60mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	1W
IP Rating	IP44
Light Source	LED built in
Cable Length	12cm
F Mark	F

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	2,5V
Safety Class	
Power(Watts)	0,9W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 3535
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1-4VV
Power Factor	0,5
Constant Current	Yes
350mA	2,8-11V
IP Rating	IP20
Safety Class	
Housing Material	Plastic
Brand	One Light
Ilumination Data	
Colour Tamparatura	20001/
Colour Temperature	3000K
Light Efficiency	80lm 80lm/\/
Light Efficiency	80lm/W
CRI	90

Dark Light	Yes	
acking Info		
Pcs/Carton	1	
Barcode	5291889062868	
HS Code	9405409900	
ertification & Warranty		
Warranty	3 Years	

Illumination Diagram