

19 Wall Recessed & Inground>Indoor/Outdoor Dark Light Wall Recessed

68032/AL/W



3W LED recessed wall light, IP54, ideal for, indoor and outdoor, corridors and stairs illumination.

Complete with driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery




Physical Specification

Item Group	19 Wall Recessed & Inground
Family	Indoor/Outdoor Dark Light Wall Recessed
Order Code	68032/AL/W
Colour	Aluminium
Material	Natural Aluminium
Shape	Rectangular
Length	70mm

Width	70mm	
Height	45mm	
Cutout Hole Diameter	52mm	
Recessed wall	Yes	
Depth Required	110mm Concrete 50mm Gypsum	
Indoor	Yes	
Outdoor	Yes	
Adjustable	No	
Electrical Characteristics		
Gear	Built In	
Fitting I Driver		
Fitting + Driver		
Input Voltage	100-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	3W	
IP Rating	IP54	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	700mA	
Voltage	4V	
Safety Class		
Power(Watts)	2,8W	
IP Rating	IP54	
Light Source	LED built in	

LED Brand	Cree
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2,8-3,5W
Power Factor	0,5
Constant Current	Yes
700mA	4-5V
IP Rating	IP20
Safety Class	
Brand	HEP
Protection	0
Illumination Data	
Colour Temperature	3000K
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	11cm
Box Width	7,5cm
Box Height	7,5cm
Box Weight	
	0,3Kg
Pcs/Carton	0,3Kg 30
Pcs/Carton Barcode	
	30

Energy Label



Certification	& W	/arrantv
Columbation	\sim $^{\prime}$	arrarrey

Warranty	2 Years
Weee Directive	Yes