

19 Wall Recessed & Inground>Wall Recessed Pro Range

68058/W



3,7W LED recessed wall light, IP65, ideal for, indoor and outdoor, corridors and stairs illumination.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions

	195mm	Ī		94mm I I
0 [- 63mm	

Physical Specification

Item Group	19 Wall Recessed & Inground
Family	Wall Recessed Pro Range
Order Code	68058/W
Colour	Stainless Steel
Material	Stainless Steel 316
Diffuser Material	Glass
Shape	Rectangular
Length	195mm
Width	63mm
Height	94mm
Cutout Hole Width	180mm
Cutout Hole Length	58mm

Recessed wall	Yes
Depth Required	97mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	9
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3,7W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	50cm
F Mark	F
Fitting	
Input Type	Constant Current
Power(Watts)	3,7W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD
LED Brand	Nichia
LED Number	10

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,7W
Power Factor	0,5
Constant Current	Yes
IP Rating	IP20
Safety Class	
Protection	0
Illumination Data	
	3000K
Colour Temperature	3000K 46lm
Colour Temperature Lumen Output	46lm
Colour Temperature Lumen Output Light Efficiency	46lm 12,7lm/W
Colour Temperature Lumen Output Light Efficiency CRI	46lm 12,7lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	46lm 12,7lm/W
Colour Temperature Lumen Output Light Efficiency CRI	46lm 12,7lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	46lm 12,7lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	46lm 12,7lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	46lm 12,7lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	46lm 12,7lm/W 80 120°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight	46lm 12,7lm/W 80 120° C

Energy Label



Weee Directive

Certification & Warranty	
Warranty	2 Years

Yes