

## 19 Wall Recessed & Inground>Outdoor Dark Light Wall Recessed Die cast

# 68064/W/W



3,6W LED wall recessed light, IP65, ideal for both indoor and outdoor installation.

Complete with 350mA driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.













#### Downloads










#### Dimensions



#### **Physical Specification**


Item Group	19 Wall Recessed & Inground
Family	Outdoor Dark Light Wall Recessed Die cast
Order Code	68064/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	65mm
Width	107mm
Height	65mm
Cutout Hole Width	97mm
Cutout Hole Length	62mm
Recessed wall	Yes

Depth Required	65mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3,6W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	9V
Safety Class	<u> </u>
Power(Watts)	3W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD
LED Brand	Philips
LED Number	6

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1-4VV
Power Factor	0,5
Constant Current	Yes
350mA	3-10V
IP Rating	IP20
Safety Class	
Brand	Eaglerise
Protection	0
Illumination Data	
Colour Temperature	3000K
Colour Temperature  Lumen Output	85lm
Colour Temperature  Lumen Output  Light Efficiency	85lm 23,61lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	85lm 23,61lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	85lm 23,61lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	85lm 23,61lm/W 80 44°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	85lm 23,61lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	85lm 23,61lm/W 80 44°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	85lm 23,61lm/W 80 44°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	85lm 23,61lm/W 80 44°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	85lm 23,61lm/W 80 44° Yes
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length	23,61lm/W 80 44° Yes
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width	85lm 23,61lm/W 80 44° Yes  13cm 10cm

Pcs/Carton	24
Barcode	5291889039471
HS Code	9405409900

## Energy Label



### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes