

## 19 Wall Recessed & Inground>The Glass Face Recessed Lights

# 68076A/W/W



4W Glass SMD LED recessed wall light, IP65.

AC LED

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions




#### **Physical Specification**

Item Group	19 Wall Recessed & Inground
Family	The Glass Face Recessed Lights
Order Code	68076A/W/W
Colour	White
Material	Glass
Shape	Rectangular
Length	190mm
Width	80mm
Height	36mm
Cutout Hole Width	115mm
Cutout Hole Length	70mm
Recessed wall	Yes

Fitting + Driver  Input Voltage 220-240V  50 Hz Yes  60 Hz Yes  60 Hz Yes  Safety Class	Depth Required	55mm
Adjustable  Rectool Characteristos  Gear  No  Fitting + Driver  Input Voltage  50 Hz  Yes  60 Hz  Yes  Safety Class  Power(Watts)  IP Rating  Light Source  LED built in  Dimmable  F Mark  Colour Temperature  Lught Efficiency  CRI  Beam Angle  Illumination Dataan  Dark Light  Packing Info	Indoor	Yes
Gear No  Fitting + Driver  Input Voltage 20-240V  50 Hz Yes  60 Hz Yes  60 Hz Yes  Safety Class  Flower(Watts) 4W  IP Reting P65  Light Source LED built in  Dimmable No  F Mark  Colour Temperature 3000K  Lumen Output 270lm  Light Efficiency 67.5lm/W  CRI 80  Beam Angle Illumination Diagram  Dark Light  Dark Light  FY Secking Info	Outdoor	Yes
Gear  Fitting + Driver  Input Voltage 220-240V  50 Hz Yes  60 Hz Yes  Safety Class  Power(Watts) 4W  IP Rating IP65  Light Source LED built in  Dimmable No  F Mark  Colour Temperature 3000K  Lumen Output 270 in  Light Efficiency 67.5 in/W  CRI 880  Beam Angle 38°  Illumination Diagram  Dark Light 100  Packing Info	Adjustable	No
Gear  Fitting + Driver  Input Voltage 220-240V  50 Hz Yes  60 Hz Yes  Safety Class  Power(Watts) 4W  IP Rating IPP5  Light Source LED built in  Dimmable No  F Mark  Colour Temperature 3000K  Lumen Output 270 In  Light Efficiency 67.5 Im/W  CRI 880  Beam Angle 38°  Illumination Diagram  Dark Light 100  Packing Info		
Fitting + Driver  Input Voltage  200-240V  Yes  60 Hz  Yes  60 Hz  Yas  Safety Class  Power(Watts)  IP Rating  IPRating  IPRof  Light Source  LED built in  Dimmable  No  FMark  V  IUmination Data  Colour Temperature  Light Efficiency  G7. Sim/N  CRI  Beam Angle  Illumination Diagram  Dark Light  Prose  Input Voltage  220-240V  Yes  44V  Yes  44V  IVE  AND  IPROSE  INPUT  INPUT	Electrical Characteristics	
Fitting + Driver  Input Voltage  200-240V  Yes  60 Hz  Yes  60 Hz  Yas  Safety Class  Power(Watts)  IP Rating  IPRating  IPRof  Light Source  LED built in  Dimmable  No  FMark  V  IUmination Data  Colour Temperature  Light Efficiency  G7. Sim/N  CRI  Beam Angle  Illumination Diagram  Dark Light  Prose  Input Voltage  220-240V  Yes  44V  Yes  44V  IVE  AND  IPROSE  INPUT  INPUT	Coor	Na
Input Voltage  50 Hz  60 Hz  Yes  Safety Class  Power(Watts)  IP Rating  Light Source  LED built in  No  F Mark  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Tess  220-240V  Yes  4W  Yes  4W  LIPES  LIPES  LED built in  No  F Mark  F Mark  Research Angle  80  80  80  80  Packing Info	Gear	INO
So Hz For Hz Fo	Fitting + Driver	
Safety Class  Power(Watts)  IP Rating  IP65  Light Source  LED built in  Dimmable  No  F Mark  Colour Temperature  Jumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Yes  Yes   Yes   AW  AW  AW  POS  Beam Angle  Illumination Data  Yes  Yes  AW  AW  POS  Beam Angle  Jacking Info	Input Voltage	220-240V
Safety Class  Power(Watts)  IP Reting  Light Source  LED built in  No  F Mark  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Yes	50 Hz	Yes
Power(Watts)  IP Rating  IP65  Light Source  LED built in  No  F Mark  Clour Temperature  Sounce  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	60 Hz	Yes
Light Source LED built in  No FMark  FMark  Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light  Packing Info	Safety Class	
Light Source  Dimmable  F Mark  F Mark  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	Power(Watts)	4W
Dimmable F Mark  F Mark  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Juliumination Diagram  Dark Light  Packing Info	IP Rating	IP65
Illumination Data   South Program   South Pr	Light Source	LED built in
Colour Temperature 3000K  Lumen Output 270Im  Light Efficiency 67,5Im/W  CRI 80  Beam Angle 36°  Illumination Diagram  Dark Light Yes	Dimmable	No
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	F Mark	F
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info		
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	Illumination Data	
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	Colour Temperature	3000K
CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	Lumen Output	270lm
Beam Angle  Illumination Diagram  Dark Light  Packing Info	Light Efficiency	67,5lm/W
Dark Light  Packing Info	CRI	80
Dark Light  Packing Info	Beam Angle	36°
Packing Info	Illumination Diagram	
	Dark Light	Yes
	Packing Info	
Pcs/Carton 12		40
	Pcs/Carton	12

Barcode	5291889059448
HS Code	9405409900

## Energy Label



### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes