

21 Industrial & Floodlights>The COB LED Street Light 20-80W

70100/AN/C



LED street light with COB LED. High lumen output ideal for replacement of old HPS and mercury street lighting fittings.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The COB LED Street Light 20-80W
Order Code	70100/AN/C
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	215mm
Width	500mm
Height	85mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	60cm
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1500mA
Voltage	32V
Power(Watts)	48W
IP Rating	IP65
Light Source	LED built in
LED Type	COB
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	43,5-58,5W

Power Factor	0,9
Constant Current	Yes
1500mA	29-36V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	SELF

Illumination Data


Colour Temperature	4000K
Lumen Output	3750lm
Light Efficiency	75lm/W
CRI	70
Beam Angle	120° x 60°
Illumination Diagram	

Packing Info Box Weight 2,5Kg Pcs/Carton 2

Barcode 5291889034629

HS Code 9405409900

Energy Label



Certification & Warranty	
Certification & Warranty	
Warranty	3 Years
Weee Directive	Yes