

21 Industrial & Floodlights>The LED Park Lantern Die cast

70110/AN/C



LED outdoor light for poles 3m and higher. Ideal for parks, parkings, playgrounds.

Supplied with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery




Physical Specification

Item Group	21 Industrial & Floodlights
Family	The LED Park Lantern Die cast
Order Code	70110/AN/C
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	425mm

Width	425mm
Height	820mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
ectrical Characteristics	
ocinical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	60W
IP Rating	IP66
Light Source	LED built in
Dimmable	No
Cable Length	100cm
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1700mA
Voltage	35V
Power(Watts)	59,5W
IP Rating	IP66
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Cree

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	46-92W
Power Factor	0,9
Constant Current	Yes
1700mA	27-54V
IP Rating	IP65
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Meanwell
Illumination Data	
Colour Temperature	4000K
	4000K 4500lm
Colour Temperature	
Colour Temperature Lumen Output	4500lm
Colour Temperature Lumen Output Light Efficiency	4500lm 75lm/W
Colour Temperature Lumen Output Light Efficiency CRI	4500lm 75lm/VV
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4500lm 75lm/W 70 Assymetric
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4500lm 75lm/W 70 Assymetric
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4500lm 75lm/VV 70 Assymetric
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight	4500lm 75lm/W 70 Assymetric
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4500lm 75lm/W 70 Assymetric \$\int \text{9,6Kg}\$
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight Pcs/Carton	4500lm 75lm/W 70 Assymetric 9,6Kg 1
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight Pcs/Carton Barcode	4500lm 75lm/W 70 Assymetric 9,6Kg 1 5291889051688

Energy Label



Certification & Warranty	
Warranty	5 Years
Weee Directive	Yes