

# 21 Industrial & Floodlights>The Glass Face AC LED Floodlights

# 7028BG/B/C



30W AC LED flood light with adjustable mounting bracket.

IP65 rated for outdoor use.

Complies with standard EN60598-1 and any other specific standards.




### Downloads







### Dimensions




### **Physical Specification**

Item Group	21 Industrial & Floodlights
Family	The Glass Face AC LED Floodlights
Order Code	7028BG/B/C
Colour	Black
Material	Die Cast
Diffuser Material	Glass
Shape	Rectangular
Length	200mm
Width	155mm
Height	35mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	No
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	50cm
F Mark	F
Illumination Data	
Colour Temperature	4000K
Lumen Output	2400lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	100°
Illumination Diagram	
Packing Info	
Pas/Carton	12
Pcs/Carton	12
Barcode	5291889046042

# Energy Label



Certification & Warranty	
Warranty	2 Years

Weee Directive Yes