

21 Industrial & Floodlights>The Slim Line LED Floodlights Die cast

7040/G/D



30W COB LED Slim floodlight, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification



Item Group	21 Industrial & Floodlights
Family	The Slim Line LED Floodlights Die cast
Order Code	7040/G/D
Colour	Grey
Material	Die Cast
Diffuser Material	Glass
Shape	Rectangular
Length	240mm
Width	280mm
Height	145mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground
Outdoor
Adjustable

Yes
Yes
1 Direction

Electrical Characteristics

Gear
Fitting + Driver
Input Voltage
50 Hz
60 Hz
Safety Class
Power(Watts)
IP Rating
Light Source
Dimmable
Cable Length
F Mark

Built In
100-240V
Yes
Yes

30W
IP65
LED built in
No
100cm


Fitting

Input Type
Power(Watts)
IP Rating
Light Source
LED Type
LED Brand


Constant Current
30W
IP65
LED built in
COB
Epistar

Gear

Gear Type
Input Voltage
50 Hz

Led Driver
100-240V
Yes

60 Hz
Power(Watts)
Power Factor
Constant Current
IP Rating
Safety Class
Dimmable
Housing Material
Output Terminal

Yes
30W
0,9
Yes
IP20

No
Plastic
Connector

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

6000K
2100lm
70lm/W
70
120°


Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

25cm
10cm
32cm
2,5Kg
10
5291889032779
9405409900

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes