

## 21 Industrial & Floodlights>The COB LED Design Floodlights Die cast + plastic

# 7064/W/C



10W COB LED design floodlight, IP65.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




#### Downloads







#### Dimensions



#### Gallery



#### Physical Specification


Item Group	21 Industrial & Floodlights
Family	The COB LED Design Floodlights Die cast + plastic
Order Code	7064/W/C
Colour	White
Material	Die Cast
Shape	Rectangular
Length	190mm

Width	108mm
Height	67mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	1 Direction
ectrical Characteristics	
Coor	Duilt In
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	100cm
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	320mA
Power(Watts)	10W
IP Rating	IP65
Light Source	LED built in
LED Type	СОВ

LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10W
Power Factor	0,9
Constant Current	Yes
Output	330mA
Voltage Range	30V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Output Terminal	Connector
Output Terminal  Illumination Data	Connector
Illumination Data	
Illumination Data  Colour Temperature	4000K
Illumination Data  Colour Temperature  Lumen Output	4000K 1135lm
Colour Temperature  Lumen Output  Light Efficiency	4000K 1135lm 113,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	4000K 1135lm 113,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	4000K 1135lm 113,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	4000K 1135lm 113,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	4000K 1135lm 113,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	4000K 1135lm 113,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4000K 1135lm 113,5lm/W
Illumination Data  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	4000K 1135lm 113,5lm/W 70
Illumination Data  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	4000K 1135lm 113,5lm/W 70 100°

Box Weight	1Kg
Pcs/Carton	8
Barcode	5291889045953
HS Code	9405409900

## Energy Label



### Certification & Warranty

Warranty	3 Years
Weee Directive	Yes