

## 21 Industrial & Floodlights>The COB LED Design Floodlights Die cast + plastic

# 7066/W/C



30W COB LED design floodlight, IP65.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




#### Downloads







#### Dimensions



#### Gallery



#### Physical Specification


21 Industrial & Floodlights
The COB LED Design Floodlights Die cast + plastic
7066/W/C
White
Die Cast
Rectangular
270mm

Width	128mm
Height	79mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	1 Direction
lectrical Characteristics	
Gear	Built In
Elithan a Dahan	
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	100cm
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1050mA
Voltage	25
Power(Watts)	27,5W
IP Rating	IP65
Light Source	LED built in
LED Type	СОВ

LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30W
Power Factor	0,9
Constant Current	Yes
1050mA	25V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Illumination Data	
Colour Temperature	4000K
Lumen Output	3030lm
Light Efficiency	101lm/W
CRI	70
Beam Angle	100°
Illumination Diagram	
Packing Info	
Box Length	20cm
Box Width	12,8cm
Box Height	29,3cm
Box Weight	2Kg

Pcs/Carton	4
Barcode	5291889045960
HS Code	9405409900

# Energy Label



### Certification & Warranty

Warranty	3 Years
Weee Directive	Yes