

25 Lamps>R7s LED

7604/C



4,5W R7s COB LED lamp

Halogen 78mm replacement

Complies with standard EN62560 and any other specific standards.




Downloads





Dimensions



Gallery




Physical Specification

Item Group	25 Lamps
Family	R7s LED
Order Code	7604/C
Shape	Circular
Height	78mm
Diameter	35mm

Gear	No
Lamp	
Input Type	Mains Voltage
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,5W
Lamp Type	LED
Lamp Holder	R7s
LED Type	СОВ
LED Brand	Epistar
Dimmable	No
Illumination Data	
	4000K
Colour Temperature	4000K
Colour Temperature Lumen Output	350lm
Colour Temperature Lumen Output Light Efficiency	350lm 77,78lm/W
Colour Temperature Lumen Output Light Efficiency CRI	350lm 77,78lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	350lm 77,78lm/W
Colour Temperature Lumen Output Light Efficiency CRI	350lm 77,78lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	350lm 77,78lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	350lm 77,78lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	350lm 77,78lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	350lm 77,78lm/W 80 180°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	350lm 77,78lm/W 80 180° 6,6cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	350lm 77,78lm/W 80 180° 6,6cm 4,7cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	350lm 77,78lm/W 80 180° 6,6cm 4,7cm 8,4cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	350lm 77,78lm/W 80 180° 6,6cm 4,7cm 8,4cm 0,07Kg

Electrical Characteristics

Energy Label



Energy Consumption

4,5kWh/1000h

Certification & Warranty

Warranty	2 Years
Average Lifetime	35000hours
Switching Cycles	60000
Weee Directive	Yes